



QJ-VR & PTC-VR VARIABLE RATE

FERTILIZER NOZZLES

TIP PART NO.	CAPACITY ONE TIP IN l/min	APPLICATION RATE FOR 50 cm SPRAY TIP SPACING											APPLICATION RATE FOR 75 cm SPRAY TIP SPACING									
		l/ha																				
		4 km/h	6 km/h	8 km/h	10 km/h	12 km/h	16 km/h	20 km/h	25 km/h	30 km/h	35 km/h	4 km/h	6 km/h	8 km/h	10 km/h	12 km/h	16 km/h	20 km/h	25 km/h	30 km/h	35 km/h	
QJ-VR-X0.5 PTCVR-X0.5	1.0	0.41	123	82.0	61.5	49.2	41.0	30.8	24.6	19.7	16.4	14.1	82.0	54.7	41.0	32.8	27.3	20.5	16.4	13.1	10.9	9.4
	1.5	0.51	153	102	76.5	61.2	51.0	38.3	30.6	24.5	20.4	17.5	102	68.0	51.0	40.8	34.0	25.5	20.4	16.3	13.6	11.7
	2.0	0.63	189	126	94.5	75.6	63.0	47.3	37.8	30.2	25.2	21.6	126	84.0	63.0	50.4	42.0	31.5	25.2	20.2	16.8	14.4
	2.5	0.71	213	142	107	85.2	71.0	53.3	42.6	34.1	28.4	24.3	142	94.7	71.0	56.8	47.3	35.5	28.4	22.7	18.9	16.2
	3.0	0.81	243	162	122	97.2	81.0	60.8	48.6	38.9	32.4	27.8	162	108	81.0	64.8	54.0	40.5	32.4	25.9	21.6	18.5
	3.5	0.92	276	184	138	110	92.0	69.0	55.2	44.2	36.8	31.5	184	123	92.0	73.6	61.3	46.0	36.8	29.4	24.5	21.0
	4.0	1.03	309	206	155	124	103	77.3	61.8	49.4	41.2	35.3	206	137	103	82.4	68.7	51.5	41.2	33.0	27.5	23.5
	5.0	1.28	384	256	192	154	128	96.0	76.8	61.4	51.2	43.9	256	171	128	102	85.3	64.0	51.2	41.0	34.1	29.3
	6.0	1.58	474	316	237	190	158	119	94.8	75.8	63.2	54.2	316	211	158	126	105	79.0	63.2	50.6	42.1	36.1
7.0	1.96	588	392	294	235	196	147	118	94.1	78.4	67.2	392	261	196	157	131	98.0	78.4	62.7	52.3	44.8	
QJ-VR-X1.0 PTCVR-X1.0	1.0	0.62	186	124	93.0	74.4	62.0	46.5	37.2	29.8	24.8	21.3	124	82.7	62.0	49.6	41.3	31.0	24.8	19.8	16.5	14.2
	1.5	0.80	240	160	120	96.0	80.0	60.0	48.0	38.4	32.0	27.4	160	107	80.0	64.0	53.3	40.0	32.0	25.6	21.3	18.3
	2.0	1.00	300	200	150	120	100	75.0	60.0	48.0	40.0	34.3	200	133	100	80.0	66.7	50.0	40.0	32.0	26.7	22.9
	2.5	1.22	366	244	183	146	122	91.5	73.2	58.6	48.8	41.8	244	163	122	97.6	81.3	61.0	48.8	39.0	32.5	27.9
	3.0	1.46	438	292	219	175	146	110	87.6	70.1	58.4	50.1	292	195	146	117	97.3	73.0	58.4	46.7	38.9	33.4
	3.5	1.72	516	344	258	206	172	129	103	82.6	68.8	59.0	344	229	172	138	115	86.0	68.8	55.0	45.9	39.3
	4.0	2.00	600	400	300	240	200	150	120	96.0	80.0	68.6	400	267	200	160	133	100	80.0	64.0	53.3	45.7
	5.0	2.61	783	522	392	313	261	196	157	125	104	89.5	522	348	261	209	174	131	104	83.5	69.6	59.7
	6.0	3.31	993	662	497	397	331	248	199	159	132	113	662	441	331	265	221	166	132	106	88.3	75.7
7.0	4.08	1224	816	612	490	408	306	245	196	163	140	816	544	408	326	272	204	163	131	109	93.3	
QJ-VR-X2.0 PTCVR-X2.0	1.0	1.78	534	356	267	214	178	134	107	85.4	71.2	61.0	356	237	178	142	119	89.0	71.2	57.0	47.5	40.7
	1.5	2.17	651	434	326	260	217	163	130	104	86.8	74.4	434	289	217	174	145	109	86.8	69.4	57.9	49.6
	2.0	2.58	774	516	387	310	258	194	155	124	103	88.5	516	344	258	206	172	129	103	82.6	68.8	59.0
	2.5	3.01	903	602	452	361	301	226	181	144	120	103	602	401	301	241	201	151	120	96.3	80.3	68.8
	3.0	3.45	1035	690	518	414	345	259	207	166	138	118	690	460	345	276	230	173	138	110	92.0	78.9
	3.5	3.92	1176	784	588	470	392	294	235	188	157	134	784	523	392	314	261	196	157	125	105	89.6
	4.0	4.41	1323	882	662	529	441	331	265	212	176	151	882	588	441	353	294	221	176	141	118	101
	5.0	5.44	1632	1088	816	653	544	408	326	261	218	187	1088	725	544	435	363	272	218	174	145	124
	6.0	6.55	1965	1310	983	786	655	491	393	314	262	225	1310	873	655	524	437	328	262	210	175	150
7.0	7.75	2325	1550	1163	930	775	581	465	372	310	266	1550	1033	775	620	517	388	310	248	207	177	

Note: Always double check your application rates. Tabulations are based on spraying water at 21°C. See technical information (pages 179–202) for useful formulas and other technical information.

SPEED RANGE FOR VARIOUS APPLICATION RATES

TIP PART NO.	GROUND SPEED RANGE (km/h) FOR 50 cm SPACING																GROUND SPEED RANGE (km/h) FOR 75 cm SPACING															
	100 l/ha		200 l/ha		300 l/ha		400 l/ha		500 l/ha		600 l/ha		700 l/ha		800 l/ha		100 l/ha		200 l/ha		300 l/ha		400 l/ha		500 l/ha		600 l/ha		700 l/ha		800 l/ha	
	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX	MIN	MAX
QJ-VR-X0.5 PTCVR-X0.5	4.9	24	2.5	12	1.6	8	1.2	5.9	1.0	4.7	0.8	3.9	0.7	3.4	0.6	2.9	3.3	16	1.6	7.8	1.1	5.2	0.8	3.9	0.7	3.1	0.5	2.6	0.5	2.2	0.4	2.0
QJ-VR-X1.0 PTCVR-X1.0	7.4	49*	3.7	24	2.5	16	1.9	12	1.5	10	1.2	8.2	1.1	7.0	0.9	6.1	5.0	33	2.5	16	1.7	11	1.2	8.2	1.0	6.5	0.8	5.4	0.7	4.7	0.6	4.1
QJ-VR-X2.0 PTCVR-X2.0	21.4	93*	11	47*	7.1	31	5.3	23	4.3	19	3.6	16	3.1	13	2.7	12	14	62*	7.1	31	4.7	21	3.6	16	2.8	12	2.4	10	2.0	8.9	1.8	7.8

*For safest application, recommended maximum speed is 35 km/h.